

SPECIFICATIONS

THICKNESS	0.785 in (19.8 mm)		
GRADES	Select & Better, Pacific, Instinct		
WIDTHS	2 1/4 in (57.15 mm)	3 1/4 in (82.55 mm)	4 1/4 in (107.95 mm)
LENGTHS minimum and maximum	10 in* to 81 in (254 mm to 2057 mm)	10 po* to 75 in (254 mm to 1905 mm)	10 po to 81 in (254 mm to 2057 mm)
TOLERANCE on width (+/-)	0.010 in (0.254 mm)		
MOISTURE CONTENT	6% to 8%		
RELATIVE HUMIDITY REQUIRED	37% to 45%		

*Except for products in the Select & Better grade :
these products have a **minimum length of 12 in (305 mm)**.

SPECIES

	JANKA TEST* (lbs/in)	Stability Rating	FSC® Availability	WEIGHT (lbs/ft ²)	WEIGHT (sq/m ²)
BIRCH	1260	Good	yes	2.60	12.71
RED OAK	1290	Very good	yes	2.90	14.21
MAPLE	1450	Good	yes	3.00	14.75
ASH	1320	Very good	yes [†]	2.75	13.46
SILVER MAPLE	950	Good	yes	2.60	12.71
WALNUT	1010	Excellent	no	2.65	12.97

Ref. : A.Alden, H., Hardwoods of North America, USDA, General Technical Report, FPL-GTR-83

[†]Subject to availability

*The higher the number, the harder the wood. The Janka hardness test measures the force required to embed 0.444 steel ball into wood.

WARRANTY

Lifetime structural warranty.

INSTALLATION

Nailed or stapled down (flooring nails or staples must be of 1 1/2 in (38 mm) long)

SANDING



Up to 7 times

PACKAGING

	Quantity per Bundle	Bundle Size (length x width x height)	Quantity per Skid	Skid Size (length x width x height*)
2 1/4 in (57.15 mm)	20 ft ² (1.86 m ²)	85 1/2 in x 9 3/4 in x 3 1/4 in (217 cm x 24.9 cm x 8.1 cm)	1040 ft ² (96.62 m ²)	85 1/2 in x 39 in x 46 1/4 in (217 cm x 99.6 cm x 117.48 cm)
3 1/4 in (82.55 mm)	20 ft ² (1.86 m ²)	79 1/2 in x 10 1/2 in x 3 1/4 in (202 cm x 26.5 cm x 8.1 cm)	1040 ft ² (96.62 m ²)	79 in x 42 in x 45 1/8 in (201 cm x 107 cm x 114.62 cm)
4 1/4 in (107.95 mm)	19 ft ² (1.77 m ²)	85 1/2 in x 9 3/4 in x 3 1/4 in (217 cm x 24.9 cm x 8.1 cm)	988 ft ² (91.79 m ²)	85 1/2 in x 39 in x 45 1/8 in (217 cm x 99 cm x 114.62 cm)

*Height with block

CHARACTERISTICS AND ADVANTAGES

PG Hardwood Flooring Inc. manufactures unfinished hardwood flooring boards for factory finishing or finishing on the premises once installed. Backed by more than 40 years of experience, PG chooses only the very best hardwood suppliers and applies the highest industry standards to grading in order to deliver exceptional quality flooring. PG, an industry reference, uses only the finest hardwood species.

Consistency

Thanks to cutting-edge equipment, PG is an industry leader in the precision of board thickness. In other words, PG® flooring boards are the industry's Smoothest, most equal boards when compared to each other. In addition, very strict classification standards are applied at PG in compliance with the most stringent tolerance standards in the industry. The result is a truly deficiency-free consistent grade.

Raw Material Optimization

PG has embraced greening, seeking to do more with less. Optimization systems based on computer vision allow us to obtain the best yield ever achieved by a North American manufacturer. More boards using fewer trees: now that is a refreshing goal!

Flexibility

To deliver high-quality products, our equipment combines infinite flexibility in the definition of lists of possible cuts and restriction of defects with efficient, consistent production of all product types.

Each purchase of one of our flooring products will offer you peace of mind.