

### MAKING MINOR REPAIRS TO A BOARD

#### PREPARATION

- Clean the damaged area with the cleaner.

#### WAX STICK (To be used only if necessary)

Use only if the damaged section is deep and requires filling.

- Rub the stick in the defect.
- Remove surplus wax using a stiff piece of cardboard or a spatula.

#### COLOURED OIL

- Shake the container. Apply the product to the surface. Wipe away excess surface oil with a clean cloth.
- Allow to dry 24 hours.

#### FINISHING OIL

- Shake the container. Apply the product to the surface. Wait 5 minutes. Wipe away excess surface oil with a clean cloth.



### REPAIR A FLOOR

If your floor has a localized area of wear too big to use the repair kit, proceed as follows. Apply green masking tape to neighbouring boards. Carefully cover the micro-v joints. If stain is applied to the joints they will change colour (become darker). Then follow the steps in the appropriate finishing guide to restore your floor. Sanding of the localized area can be done manually.

### PARTIALLY REFRESH YOUR FLOOR

- 1- The surface must be clean and free of wax, oil, varnish, etc.
- 2- Sand lightly using a polisher (green Scotch-Brite®). Polish left to right. Do not remain in one place.
- 3- Apply a coat of finishing oil and allow to dry 24 hours.

### COMPLETELY RESTORE YOUR FLOOR

- 1- The surface must be clean and free of wax, oil, varnish, etc.
- 2- To reach the natural colour of the wood, sand the floor three times with a floor sander. Use 80 grit sandpaper for the first sanding, 120 grit for the second and 150 grit for the third.
- 3- Then follow the instructions in the appropriate finishing guide starting at step 2.

**IMPORTANT :** You may use the finishing oil alone, but the use of coloured oil† must be followed by the use of finishing oil\*.

In high traffic areas, two coats of finishing oil\* at 24 hours intervals may be applied.

The next day you may walk carefully on the floor. However, laying out furniture (with felt protectors on legs) and daily maintenance should take place only 7 to 10 days after the last application of the finishing oil. The coloured† and finishing oils may also be used to finish furniture, stairs and mouldings, etc.

Following the installation of the flooring, wait 7 to 10 days before cleaning the floor and installing furniture and carpets.

#### † Coloured oil (colour) :

Oilstain+ for stains Meteora and Sanibel.  
Primol for stains Dion, Garneau, Oliver, Pelletier, Clan, Familia and Naïve.  
Coloured base for Naïve.

#### \* Finishing oil :

Oilcraft+ for stains Meteora and Sanibel.  
Greenol for stains Dion, Garneau, Oliver, Pelletier, Clan, Familia and Naïve.  
Coloured base for Naïve.

**CAUTION:**  
TO AVOID SPONTANEOUS  
COMBUSTION, IT IS  
IMPORTANT TO SOAK  
OIL-FILLED CLOTHS  
WITH WATER PRIOR  
TO DISPOSAL.

